



Order number: BT-QMB6-H-2

Hersteller: BeamTec

Gewicht: 0.15 kg

QMB6 Dual Thickness Monitor with Oscillator

€865.00 *

Prices plus VAT [plus shipping costs](#)

Ready to ship today,

Delivery time appr. 1-3 workdays

Product information

"QMB6 Dual Thickness Monitor with Oscillator"

Dual Thickness Monitor with integrated oscillators - RS232 version

includes 1 integrated oscillator for 6 MHz quartzes; supports 2x external oscillators or 1 external and 1 integrated oscillators

high resolution measurement unit with serial link RS232

2x BNC connector for connecting 2 quartzes simultaneously

power supply : 12-

24VDC; 12V supply included

resolution: 0,01 Hz @ 10 Hz samplig rate

sampling rate: 0.5, 1, 2, 4, 10 Hz

Dimensions/weight:

61x26x106; 0.2 kg

Interface: RS232

Resolution: High

Related links to "QMB6 Dual Thickness Monitor with Oscillator"

• - [Do you have any questions concerning this product?](#)

• - [Further products by](#)

[BeamTec](#)

Available downloads:

• [Download](#)

[BT QMB6 H 2 datasheet.pdf](#)

Mehr Bilder zu "QMB6 Dual Thickness Monitor with Oscillator"

